

# Mobile Field Shelter Specifications

(ALL PRICES INCLUDE VAT)

**Assumes steel 80x40 skids all sizes are approximate for guidance only,**

- Height to eaves ex onduline 2405mm (APPROX 8')
- Height to apex ex onduline 2900mm (APPROX 10')
- External depth of: 12' building 3756mm / 10' building 3156mm
- Overhang length of 12' building 1050mm (1200mm with gutter / 10' building 650mm (800mm with gutter)
- All timbers, including framework are pressure treated - 75x50mm (3"x2") CLS framework (PRESSURE TREATED)
- ex19x125mm shiplap cladding (PRESSURE TREATED)
- 100x50mm (4"x2") CLS apex structure (PRESSURE TREATED)
- 100x50mm (4"x2") PAR timber purlins (PRESSURE TREATED)
- 125x50mm & 150x50mm purlins for 14' and 16' buildings respectively
- 11mm OSB kickboards to 1.22m (4') – other options available
- Genuine black Onduline roof lined with 11mm OSB support lining to prevent sagging
- Overhangs (FRONT CANOPY) lined with 9mm ply
- 1.880m wide x 2095mm high opening(s) to front
- Single opening up to 14' wide units, Two openings on buildings 16' to 24' wide

## Available as optional extras:

- Guttering with down pipe (2 METRE)
- Other skid options
- Roof light (CLEAR ROOF SHEET)
- Aperture surround chew strips
- Softwood lined overhang
- Double gable end vent
- Anchoring systems
- Weatherboard Cladding
- 18mm kickboards OSB (OTHER OPTIONS AVAILABLE)
- Coloured onduline
- Other roof options
- Bespoke design service available
- Partition and Front gates
- Slip Rails (SET 2)