

Mobile Field Shelter Specifications

(ALL PRICES INCLUDE VAT)

Assumes standard steel 80x40 skids

- Height to eaves inc onduline 2405MM (APPROX 8')
- Height to apex inc onduline 2900MM (APPROX 10')
- External depth of: 12' building 3756MM / 10' building 3156MM
- Overhang length of 12' building 1060MM (1200MM with gutter / 10' building 650MM (800MM with gutter)
- All timbers, including framework are pressure treated
- 75x50MM (3"x2") CLS framework (PRESSURE TREATED)
- ex19x125MM shiplap cladding (PRESSURE TREATED)
- 100x50MM (4"x2") CLS apex structure (PRESSURE TREATED)
- 100x50MM (4"x2") sawn timber purlings (PRESSURE TREATED) - 125x50MM & 150x50MM for 14' and 16' buildings respectively
- 11MM OSB kickboards to 1.22M (4') - other options available
- Genuine black Onduline roof lined with 11MM osb support lining to prevent sagging
- Overhangs (FRONT CANOPY) lined with 9MM ply
- 1.880M wide x 2095MM high opening(s) to front
- Single opening up to 14' wide units, Two openings on buildings 14'to 24' wide

Available as optional extras:

- Guttering with down pipe (2 METRE)
- Other skid options
- Roof light (CLEAR ROOF SHEET)
- Aperture surround chew strips
- Softwood lined overhang
- Double gable end vent
- Anchoring systems
- Weatherboard Cladding
- 18MM kickboards osb (OTHER OPTIONS AVAILABLE)
- Coloured onduline
- Other roof options
- Bespoke design service available
- Partition and Front gates
- Slip Rails (SET 2)

Please ask for more details, please note all sizes are nominal