

Timber Door Specifications

(ALL PRICES INCLUDE VAT)

- Frame - External 1.340m x 2.180m
- Frame – Internal 1.23mm x 2.125m
- Clad with ex19x125mm V jointed tongue and grooved planed timber
- 28mm internal framework
- Hot dipped galvanised ironmongery
- 50mm chew strip to top of bottom door
- 600mm heavy tee hinges
- Top or bottom door lined internally with 12mm exterior grade plywood
- 150mm Brenton bolt (TOP DOOR)
- 200mm auto animal bolt (BOTTOM DOOR)
- Kick-over latch (BOTTOM DOOR)
- 150mm cabin hook (TOP AND BOTTOM DOORS)
- Bottom door height 1.2m

Tack room door

- 2095mm (H) x 895mm (W)
- Clad with ex19x125mm V jointed tongue and grooved planed timber
- Framework 3 horizontal 2 angled braces
- Hot dipped galvanised ironmongery
- 3x 600mm Tee hinges
- 150mm Brenton bolt
- 200mm staple and hasp (OPTIONAL)
- 150mm cabin hooks

Double doors

- 2.1m (H) x 2.4m (w)
- Clad with ex19x125mm V jointed tongue and grooved planed timber
- 28mm framework 3 horizontal 2 angled braces
- Hot dipped galvanised ironmongery
- 3x 600mm Tee hinges per door
- 150mm Brenton bolt
- 150mm spring bolt internal (TOP)
- 300mm drop bolt internal (BOTTOM)
- 150mm cabin hooks to each door
- Cover strip cover join in doors

Rear top door

- Frame – 1140mm (W) x 910mm (H)
- Clad with ex19x125mm V jointed tongue and grooved planed timber
- Framework – full frame with angled brace
- Hot dipped galvanised ironmongery
- 2x 600mm Tee hinges
- 100mm Oval Padbolt bolt
- 150mm cabin hooks

