

Stable Specifications

(ALL PRICES INCLUDE VAT)

Assumes stables will be on a level concrete base with a single course of bricks (unless mobile). This will need to be prepared to the specifications of our supplied brickwork plans prior to delivery and installation.

Stables

- Height to eaves (excl Onduline) 2360MM
- Height to apex (excl Onduline) 2900MM
- Depth of 12' building 3756MM / 10' building 3156MM
- Overhang length of 12' Deep building 1044MM / 10' Deep building 650MM
- All timbers, including framework, is pressure treated
- 75MM x 50MM (3" x 2") CLS framework
- ex 19MM x 125MM premium redwood shiplap cladding
- 100v x 50MM (4" x 2") CLS apex structure
- 100MM x 47MM (4" x 2") c24 timber purlins
- 125MM x 47MM & 150MM x 47MM for 14' and 16' buildings)
- 11MM OSB kickboards to 1.22M (4') – other options available
- Black Genuine Onduline roof lined with 11MM OSB support lining to prevent sagging
- Overhangs lined with 9MM ply
- Ex 100MM x 75MM profiled door posts (4" x 3")
- 1200MM (4') high bottom stable door inc. 50MM chewstrip to door only complete with all ironmongery

Feedroom

- Unlined Internally
- 1800mm - 2400mm opening

Tackroom

- Unlined Internally
- 900mm Wide x 2095mm High Door

Available as optional extras:

- Top doors inc. galvanised door furniture
- Guttering with down pipe
- Galvanised steel skids (Mobile Stable)
- Roof light (Clear roof sheet)
- Door surround chew strips
- Softwood lined overhang
- Extended overhang with posts
- Increase framework to 4x2 cls
- Gable end vent
- Talk grill
- 18MM kickboard
- Fixed vent window with grill
- Coloured onduline
- Other roof options
- Bespoke design service available
- Weatherboard cladding

Please ask for more details, please note all sizes are nominal